



**TECHNICAL DATA.**

**MATERIALS**

End ring and end cap: Zinc plated Steel  
 Inner core: Zinc plated Steel

**FILTER ELEMENT CHARACTERISTIC**

Oil Flow. From: External / To: Internal  
 Filter Media: Cellulose 25 µm (c) β >2 ISO 16889  
 Filter Area: 3810 cm<sup>2</sup>  
 Collapse Pressure: Min. Δp 21 bar (2,1 MPa)

**TEMPERATURE (ISO 2943)**

Working Temperature. From: -25 °C / To: +110 °C

**COMPATIBILITY (ISO 2943)**

Full with fluids: HH-HL-HM-HV-HTG  
 (according to ISO 6743/4)

**PACKING**

Packaging Filter in a single box

Rev.	Description/Description	Date/Date	App.
(Prodotto/Product)	SPI		
(Materiale/ Material)	PLANET FILTERS S.p.A. Bolgare BG – ITALY		
—	Disegnato Design	Data/Date	Nome/ By
	12/06/06	12/06/06	Zanelli M.
—	Contr. Check	12/06/06	Belotti
	20/10/97	20/10/97	Camossi
Tolleranze generali			
Generalized tolerance			
ISO 2768-fk			
(Peso) (Weight)	(Scala) (Scale)	1:1	
Disegno grezzo: Casting:		Sostituito da: Replaces:	
		N° Disegno/Part N°	034.0034.3
		Rev.	1/1
		Tavola. Table.	
		1/1	