



TECHNICAL DATA.

MATERIALS

End rings: Polyamide
 Inner core: Tin-plate
 Gasket: NBR 70 Sh. A ± 5

FILTER ELEMENT CHARACTERISTIC

Oil Flow. From: External / To: Internal
 Filter Media: Wire mesh 60 μm
 Filter Area: 1967 cm^2
 Collapse Pressure: Min. Δp 10 bar (1 MPa)

TEMPERATURE (ISO 2943)

Working Temperature. From: $-25\text{ }^\circ\text{C}$ / To: $+110\text{ }^\circ\text{C}$

VALVES (ISO 3968)

BY-PASS / Opening Pressure: 1,7 bar $\pm 10\%$

COMPATIBILITY (ISO 2943)

Full with fluids: HH-HL-HM-HV-HTG
 (according to ISO 6743/4)

PACKING

Packaging Filter in a single box

APPROVATO

Belotti 07-03-06

N°	MODIFICHE	Proposta	Data	CODICE UGUAGLIANZA	
				Materiale	—
				Stato	—
				Trattam.	—
				sostituisce il DIS. N°	sostituito dal DIS. N°
				CODICE	
				002.1859.6	

PLANET FILTERS S.p.A.	Gruppo Filtri Speciali			
	Particolare Elemento filtrante			
	Peso del pezzo in Kg			
	Grezzo	Lavorato		
scala 1 : 1	Disegnatore Belotti			
	Controllato A.F.			
	Data 07-03-06			