

Part number:

**HYDROMA**

HYDRAULICKÉ SYSTÉMY

**HIDROMA  
SYSTEMS**

UKŁADY HYDRAULICZNE

**HYDROMA**

ГИДРАВЛИЧЕСКИЕ СИСТЕМЫ

### Pressure switch with change-over contact Type 602

Flat-pin terminal 6.3  
Width across flats 27  
Height without plug 52  
Length of thread 9



Pg 9 with strain relief  
optionally with coupler plug  
plug connection swivelling 6 x 60°

Type = reference number	602-2	602-10	602-20	602-50	602-100 M	602-100	602-200
Range of adjustment, bar	0.2-2	1-10	2-20	5-50	10-100	10-100	20-200
Overpressure safety		100 bar		300 bar			600 bar
Seal*			diaphragm				rotary seal
Reproducibility	~ 2-5%						
Hysteresis	~ 20%			smaller upon request			
Switching element		change-over contact					
Switching frequency	200/min						
Voltage, max.	250 volt						
Current, max.	6 amp.						
Type of protection	IP 65						
Temperature, permissible	-20° to +80° C						
Weight	0.12 kg						
Thread	G 1/4", M 12x1.5, M 10x1 tapered.						

The functions breaking, making or changing relate to rising pressure.

\* Please indicate medium in your order.